


Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Charcoal, Almond, Pearl Grey & Alabaster
Product Code	
Format	10.01 Full
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	90
Height (mm)	190
Size	390x90x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	25
Weight	11.164
Units Per Tonne	90.909090909091
Units Per Pallet	180
Units per Square Metre	12.5
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	150
Solar Absorption Rating	0.87
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240
Integrity	60
Insulation	60


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Charcoal, Pearl Grey & Alabaster
Product Code	
Format	15.42 Recessed Web
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	140
Height (mm)	190
Size	390x140x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	25
Weight	12.5
Units Per Tonne	80
Units Per Pallet	144
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	140
Solar Absorption Rating	0.87
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240
Integrity	Hollow: 60. Core Filled: 120
Insulation	Hollow: 60. Core Filled: 120


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Charcoal, Alabaster, Pearl Grey & Almond
Product Code	
Format	15.01 Full
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	140
Height (mm)	190
Size	390x140x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	25
Weight	12.835
Units Per Tonne	71.942446043166
Units Per Pallet	120
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	186
Solar Absorption Rating	0.87
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240
Integrity	60
Insulation	60


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Alabaster, Almond, Charcoal & Pearl Grey
Product Code	
Format	50.31 Capping Unit
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	190
Height (mm)	40
Size	390x190x40
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	6.74
Units Per Tonne	153.84615384615
Units Per Pallet	270
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.48
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Alabaster, Charcoal, Almond & Pearl Grey
Product Code	
Format	20.71 Half Height
Place of Manufacture	-
Length (mm)	390
Width (mm)	190
Height (mm)	90
Size	390x190x90
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	125
Units Per Pallet	180
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.48
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240
Integrity	60
Insulation	60


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Pearl Grey, Almond, Charcoal & Alabaster
Product Code	
Format	20.42 Recessed Web
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	30
Weight	14.1
Units Per Tonne	65.789473684211
Units Per Pallet	90
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	199
Solar Absorption Rating	0.69
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240
Integrity	Hollow: 60. Core Filled: 120
Insulation	Hollow: 60. Core Filled: 120


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Alabaster, Charcoal, Almond & Pearl Grey
Product Code	
Format	10.31 Solid
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	90
Height (mm)	190
Size	390x90x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	14.8
Units Per Tonne	67.567567567568
Units Per Pallet	144
Units per Square Metre	12.5
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.48
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.

Product Details

Product Range	Architec Polished
Texture Finish	Polished
Colours	Almond, Pearl Grey, Charcoal & Alabaster
Product Code	
Format	20.01 Full
Place of Manufacture	Oakdale, New South Wales
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	30
Weight	14.483
Units Per Tonne	65.789473684211
Units Per Pallet	90
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	199
Solar Absorption Rating	0.55
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240
Integrity	60
Insulation	60

Notes

Maximum slenderness ratio (srf) from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999.