

Vertico Split Face Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Units per sqm	Pack Size	Characteristic Unconfined Compressive Strength	Durability Class	Solar Absorption	Lrv
Vertico Split Face	Pebble			NSW	390	216	190	15.81				Exposure Grade	0.57	
Vertico Split Face	Limestone			NSW	390	216	190	15.81				Exposure Grade	0.39	
Vertico Split Face	Limestone			NSW	390	216	190		50			Exposure Grade	0.39	
Vertico Split Face	Pewter			NSW	390	216	190	15.81				Exposure Grade	0.84	
Vertico Split Face	Porcelain			NSW	390	216	190		50			Exposure Grade	0.41	
Vertico Split Face	Pewter			NSW	390	216	190	17		90	>15	Exposure Grade	0.84	19.7
Vertico Split Face	Pottery			NSW	390	216	190	17		90	>15	Exposure Grade		
Vertico Split Face	Nickel			NSW	390	216	190	17		90	>15	Exposure Grade	0.65	30.3
Vertico Split Face	Porcelain			NSW	390	216	190	15.81				Exposure Grade	0.41	
Vertico Split Face	Pottery			NSW	390	216	190					Exposure Grade		
Vertico Split Face	Pebble			NSW	390	216	190	17		90	>15	Exposure Grade	0.57	34
Vertico Split Face	Pewter			NSW	390	216	190		50			Exposure Grade	0.84	
Vertico Split Face	Limestone			NSW	390	216	190	17		90	>15	Exposure Grade	0.39	51.8
Vertico Split Face	Nickel			NSW	390	216	190	15.81				Exposure Grade	0.65	
Vertico Split Face	Pebble			NSW	390	216	190		50			Exposure Grade	0.57	
Vertico Split Face	Porcelain			NSW	390	216	190	17		90	>15	Exposure Grade	0.41	57.9

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.