

GB Vertico Honed Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Pack Size	Characteristic Unconfined Compressive Strength	Durability Class	Solar Absorption
GB Vertico Honed	Porcelain			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pottery			NSW	390	190	190				Exposure Grade	0.65
GB Vertico Honed	Nickel			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pebble			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pebble			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Nickel			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Limestone			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Limestone			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Porcelain			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Nickel			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pewter			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pewter			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pottery			NSW	390	190	190				Exposure Grade	0.65
GB Vertico Honed	Porcelain			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Limestone			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Honed	Pottery			NSW	390	190	190	15.6	90	>15	Exposure Grade	
GB Vertico Honed	Pewter			NSW	390	190	190	15.6			Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Pack Size	Characteristic Unconfined Compressive Strength	Durability Class	Solar Absorption
GB Vertico Honed	Pebble			NSW	390	190	190	15.6			Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.