

GB Vertico Smooth Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Pack Size	Characteristic Unconfined Compressive Strength	Durability Class	Solar Absorption
GB Vertico Smooth	Limestone			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Porcelain			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Porcelain			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Pewter			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Limestone			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Pottery			NSW	390	190	190				Exposure Grade	0.65
GB Vertico Smooth	Pewter			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Nickel			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Pottery			NSW	390	190	190				Exposure Grade	0.65
GB Vertico Smooth	Pebble			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Pebble			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Limestone			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Porcelain			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Pebble			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Pottery			NSW	390	190	190	15.6	90	>15	Exposure Grade	
GB Vertico Smooth	Nickel			NSW	390	190	190	15.6			Exposure Grade	
GB Vertico Smooth	Nickel			NSW	390	190	190	15.6			Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Pack Size	Characteristic Unconfined Compressive Strength	Durability Class	Solar Absorption
GB Vertico Smooth	Pewter			NSW	390	190	190	15.6			Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.