

Ridgi Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Units per sqm	Durability Class
Ridgi	Galvanised Grey			NSW	900	110	60	7		General Purpose
Ridgi	Weathered Ash			NSW	1500	50	150		3.16	General Purpose
Ridgi	Galvanised Grey			NSW	1200	110	60	10		General Purpose
Ridgi	Galvanised Grey			NSW	1200	110	60	10		General Purpose
Ridgi	Galvanised Grey			NSW	900	60	60	4		General Purpose
Ridgi	Galvanised Grey			NSW	650	110	60	5.02		General Purpose
Ridgi	The Rocks			NSW	1500	50	150	31		General Purpose
Ridgi	Galvanised Grey			NSW	1500	60	60	6		General Purpose
Ridgi	Grey Smooth			NSW	1500	50	150	29		General Purpose
Ridgi	Galvanised Grey			NSW	900	110	60	7		General Purpose
Ridgi	Galvanised Grey			NSW	1500	110	60	12		General Purpose
Ridgi	Galvanised Grey			NSW	1200	60	60	5		General Purpose
Ridgi	Graphite Sandstone			NSW	1500	50	150	30		General Purpose
Ridgi	Galvanised Grey			NSW	1800	60	60	7		General Purpose
Ridgi	Galvanised Grey			NSW	1500	110	60	12		General Purpose
Ridgi	Gumtree Timberlook			NSW	1500	50	150	30.9		General Purpose
Ridgi	Galvanised Grey			NSW	650	60	60	3		General Purpose

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Units per sqm	Durability Class
Ridgi	Galvanised Grey			NSW	650	110	60	5.02		General Purpose
Ridgi	Merbau Timberlook			NSW	1500	50	150		3.16	General Purpose
Ridgi	Galvanised Grey			NSW	1800	110	60	14		General Purpose
Ridgi	Ironbark Timberlook			NSW	1500	50	150	30.9		General Purpose
Ridgi	Galvanised Grey			NSW	580	50	3	1		General Purpose
Ridgi	Galvanised Grey			NSW	1800	110	60	14		General Purpose

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.