

Architec Polished Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Units per sqm	Pack Size	Durability Class	Solar Absorption
Architec Polished	Charcoal			NSW	390	90	190	11.164	12.5		General Purpose	0.87
Architec Polished	Charcoal			NSW	390	140	190	12.5			General Purpose	0.87
Architec Polished	Charcoal			NSW	390	140	190	12.835			General Purpose	0.87
Architec Polished	Alabaster			NSW	390	190	40	6.74		252	General Purpose	0.48
Architec Polished	Alabaster			NSW	390	190	90				General Purpose	0.48
Architec Polished	Almond			NSW	390	190	40	6.74		252	General Purpose	0.55
Architec Polished	Charcoal			NSW	390	190	40	6.74		252	General Purpose	0.87
Architec Polished	Alabaster			NSW	390	140	190	12.835	12.5		General Purpose	0.48
Architec Polished	Pearl Grey			NSW	390	190	190	14.1			General Purpose	0.69
Architec Polished	Pearl Grey			NSW	390	140	190	12.5			General Purpose	0.69
Architec Polished	Alabaster			NSW	390	90	190	14.8	12.5		General Purpose	0.48
Architec Polished	Almond			NSW	390	90	190	11.164	12.5		General Purpose	0.55
Architec Polished	Charcoal			NSW	390	90	190	14.8	12.5		General Purpose	0.87
Architec Polished	Pearl Grey			NSW	390	90	190	11.325	12.5		General Purpose	0.69
Architec Polished	Almond			NSW	390	90	190	14.8	12.5		General Purpose	0.55
Architec Polished	Pearl Grey			NSW	390	140	190	12.835			General Purpose	0.69
Architec Polished	Almond			NSW	390	190	190	14.1			General Purpose	0.55

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Units per sqm	Pack Size	Durability Class	Solar Absorption
Architec Polished	Almond			NSW	390	190	190	14.483			General Purpose	0.55
Architec Polished	Alabaster			NSW	390	140	190	12.5			General Purpose	0.48
Architec Polished	Charcoal			NSW	390	190	90				General Purpose	0.87
Architec Polished	Pearl Grey			NSW	390	190	190	14.483			General Purpose	0.69
Architec Polished	Pearl Grey			NSW	390	90	190	14.8	12.5		General Purpose	0.69
Architec Polished	Charcoal			NSW	390	190	190	14.483			General Purpose	0.87
Architec Polished	Charcoal			NSW	390	190	190	14.1			General Purpose	0.87
Architec Polished	Alabaster			NSW	390	190	190	14.483			General Purpose	0.48
Architec Polished	Alabaster			NSW	390	190	190	14.1			General Purpose	0.48
Architec Polished	Pearl Grey			NSW	390	190	90				General Purpose	0.69
Architec Polished	Alabaster			NSW	390	90	190	11.164	12.5		General Purpose	0.48
Architec Polished	Almond			NSW	390	190	90				General Purpose	0.55
Architec Polished	Pearl Grey			NSW	390	190	40	6.74		252	General Purpose	0.69
Architec Polished	Almond			NSW	390	140	190	12.835	12.5		General Purpose	0.55

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.