

GB Split Face Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Durability Class	Solar Absorption	Lrv
GB Split Face	Nickel			NSW	390	290	190	22.2	Exposure Grade	0.65	
GB Split Face	Pebble			NSW	390	290	190	22.2	Exposure Grade	0.57	
GB Split Face	Pewter			NSW	390	90	190	13.5	Exposure Grade	0.84	
GB Split Face	Nickel			NSW	390	190	190	16.33	Exposure Grade	0.65	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pewter			NSW	390	290	190	22.2	Exposure Grade	0.84	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Limestone			NSW	390	290	190	22.2	Exposure Grade	0.39	
GB Split Face	Pebble			NSW	390	90	190	13.5	Exposure Grade	0.57	
GB Split Face	Pottery			NSW	390	190	190		Exposure Grade		
GB Split Face	Limestone			NSW	390	290	190	22.2	Exposure Grade	0.39	
GB Split Face	Pewter			NSW	390	190	190	20	Exposure Grade	0.84	
GB Split Face	Porcelain			NSW	390	190	190	20	Exposure Grade	0.41	
GB Split Face	Porcelain			NSW	390	190	190	16.33	Exposure Grade	0.41	
GB Split Face	Porcelain			NSW	390	290	190	22.2	Exposure Grade	0.41	
GB Split Face	Pewter			NSW	390	190	190	16.33	Exposure Grade	0.84	
GB Split Face	Nickel			NSW	390	290	190	22.2	Exposure Grade	0.65	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pebble			NSW	390	290	190	22.2	Exposure Grade	0.57	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Durability Class	Solar Absorption	Lrv
GB Split Face	Nickel			NSW	390	90	190	12.7	Exposure Grade	0.65	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Limestone			NSW	390	90	190	12.7	Exposure Grade	0.39	
GB Split Face	Porcelain			NSW	390	190	190	15.81	Exposure Grade	0.41	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pebble			NSW	390	190	190	20	Exposure Grade	0.57	
GB Split Face	Pewter			NSW	390	190	190	20	Exposure Grade	0.84	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pebble			NSW	390	190	190	16.33	Exposure Grade	0.57	
GB Split Face	Limestone			NSW	390	190	190	16.33	Exposure Grade	0.39	
GB Split Face	Limestone			NSW	390	190	190	20	Exposure Grade	0.39	
GB Split Face	Pottery			NSW	390	90	190		Exposure Grade		
GB Split Face	Porcelain			NSW	390	90	190	12.7	Exposure Grade	0.41	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Porcelain			NSW	390	290	190	22.2	Exposure Grade	0.41	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Limestone			NSW	390	190	190	15.81	Exposure Grade	0.39	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pottery			NSW	390	190	190		Exposure Grade		
GB Split Face	Porcelain			NSW	390	190	190	20	Exposure Grade	0.41	
GB Split Face	Pewter			NSW	390	290	190	22.2	Exposure Grade	0.84	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pewter			NSW	390	190	190	15.81	Exposure Grade	0.84	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

Product Range	Name	Dimension Illustration	Swatch Image	State	Length	Width	Height	Average Weight / Unit (kg)	Durability Class	Solar Absorption	Lrv
GB Split Face	Limestone			NSW	390	190	190	20	Exposure Grade	0.39	
GB Split Face	Pebble			NSW	390	190	190	20	Exposure Grade	0.57	
GB Split Face	Nickel			NSW	390	190	190	15.81	Exposure Grade	0.65	
GB Split Face	Nickel			NSW	390	190	190	20	Exposure Grade	0.65	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pebble			NSW	390	190	190	15.81	Exposure Grade	0.57	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34
GB Split Face	Pottery			NSW	390	190	190		Exposure Grade		
GB Split Face	Nickel			NSW	390	190	190	20	Exposure Grade	0.65	Porcelain - 57.9 Pewter - 19.7 Nickel - 30.3 Limestone - 51.8 Pebble - 34

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.